



PSS



Pallet Stacking Station PSS

Collect and stack perfectly

With its modular system, up to 25 pallets can be securely stacked and stored in a small space. The PSS is produced in the versions EURO, INDUSTRY, GMA, CARGO as well as CUSTOM.

The modular system of the PSS enables the construction of pallet racks in the desired height. The bot-tom module is bolted to the floor, the additional 10- and 5-pallet modules are securely screwed on top of one another.



Pallet stacking station EURO / * INDUSTRY

Specifications/technical data

| Size in mm | pallet of | | |
|-----------------------|---------------------------------------|--------|--------|
| Module | 5 | 10 | 15 |
| Length | 1000 | 1000 | 1000 |
| Width | 1020* | 1020* | 1020* |
| Inner width | 820* | 820* | 820* |
| Height | 710 | 1425 | 2140 |
| Weight kg | 110 ** | 220 ** | 330 ** |
| Number of screw holes | 14 | 14 | 14 |
| Hole width | 12,5 | 12,5 | 12,5 |
| Material PSS | Steel plate DC01 (Grade A) EN10130 | | |
| Thickness | 4 | 4 | 4 |

Technical data

Custom-made for the individual pallet system

SW Paratus offers the PSS stacking station in a variety of dimensions that are precisely adapted to standard pallet sizes. Customized dimensions for CUSTOM pallets upon request.

Each individual module consists of five assemblies/components: two side walls, one back wall, two-part reinforcing frame. Nuts and bolts used for mounting the rack (NOT mounting to floor) = M12 (zinc-plated).

Attachment to the floor on site via the screw holes (use appropriate, approved floor anchors, for example, anchor bolts or Express anchors in the case of concrete; if necessary ask structural engineer.)

* with INDUSTRY inner and outer width, add + 200 mm each

** with INDUSTRY weight add + 10 / + 20 / + 30 kg each